

A variant of the original **Softrak 65**, which has proved invaluable in managing wetland, uplands and other delicate habitats over the last 10 years, the **Softrak 75** with a 75 hp Deutz engine is designed to satisfy the needs of the contractor or reserve manager who needs to manage larger areas but still maintain the



extremely low ground pressure and minimal damage to sensitive terrains of the original. All of the options previously offered on the Softrak 65 can be fitted to the 75hp variant. The use of high strength steels means that although the **Softrak 75** is very light it is immensely strong as proven by the many thousands of hours accumulated by end users without material failures. The chassis, cab, undercarriage etc. are prepared by shot blasting, sprayed with molten zinc and then powder coated with a tough polyester paint to give an extremely durable finish.

The **Softrak 75** is fitted with the 2.9 litre 75hp Deutz TCD engine. This engine complies with the latest emission standards and is well known for its outstanding reliability and low fuel consumption. The cooling system is fitted with a large capacity aluminium radiator rated for temperatures up to 45c - 113f. The radiator and oil cooler is sited so as to minimise the intake of dust and debris generated when harvesting or mowing. The large intake grill is designed so as to catch any particle over 0.1 inch the radiator fins are sized to allow particles up to 0.11inch to pass through without causing blockages. The optional reversible fan can be activated to instantly clean off any debris collecting on the intake grills. The comfortable 3 man cab comes with rubber suspension, tinted glass, full height doors, opening side windows and sound-proofing as standard. With a full heating and ventilation system (optional air conditioning), stress free operation is ensured in all conditions. "Margard" polycarbonate front and rear safety screens with a silicone scratch resistant coating are fitted as standard. The cab is fitted with a heavy-duty suspension seat and lap belt and fixed passenger seats. The optional front linkage (with integral suspension) and hydraulic PTO enables many operations to be carried out where it is essential not to drive over the vegetation before cutting, such as reed or willow harvesting, weed cutting and mowing and mulching.

The 1322 lbs lift capacity means even heavy duty mulchers can be fitted for tackling up to 1.5 inch scrub. The removable lower lift arms can be set for independent articulation to allow float of front mounted equipment and optional double acting rams allow attachments such as bulldozer blades and snow ploughs to be fitted. The hydraulic PTO can supply up full engine horse power with flows up to 34 us.gal/min and pressure up to 5800 psi. Connections are high-pressure, easy clean, flat faced couplings for quick attachment of hoses. The **Softrak 75** front linkage allows the attachment of the same large range of tools and attachments as the Softrak 65 machine. The hydraulically tipped, rear body gives an exceptionally large payload area allowing the **Softrak 75** to carry large volumes of cut material in the chip bin (220 Bushel) whilst still keeping the centre of gravity near the middle of the tracks. This means that the weight is evenly distributed allow the track unlike other machines where, when fully laden, the rear is very heavy. This means lower ground pressure, less damage to sensitive habitats and minimises damage when turning regardless of direction of travel.

# SOFTRAK 75



The **Softrak 75** track system combines the best of a large ground contact area with the fully floating bogies to allow a smooth ride over rougher terrains. The Bridgestone rubber track used on the **Softrak 75** is unique in that the flexibility of the rubber track across its width combined with the floating bogies means that the track follows the ground contours far better than those machines with tracks comprising rigid cross bars fitted to flexible belts. This type of track tends to be far more aggressive, especially when turning. The flexible edges of the **Softrak** tracks means that they tend to ride over undulations in the ground, rather than shearing off the vegetation when turning. The cleat height can be reduced on request where high traction is not an issue.

**Technical Specifications:**

Engine: Deutz 4 cylinder turbo diesel.

Power (ISO 14396).....75 hp  
Max Torque.....354 ft - lbs  
Capacity.....177 cu.inch

**Transmission:**

Fully hydrostatic with servo operated pumps and two speed track system.

**Motors.**

Max pressure.....5800 psi  
Capacity.....2 x 45.7 cu.inch/rev

**Pumps:**

Transmission pump capacity.....2 x 3.17 cu.inch/rev  
Max pressure.....5800 psi  
Auxiliary hydraulic pumps .....0.38 cu.inch/rev to 1.22 cu.inch/rev  
Max pressure.....3625 psi  
Flow (2,300rpm).....1.66 - 11.8 us.gal/min

**Track Gear:**

Bridgestone rubber track system with fully floating bogies and hydraulic tensioning.  
Maximum Speed.....10 mph  
Ground Pressure (un-laden) .....0.097 bar (1.4psi)  
Max tractive effort.....7495 lbs  
Belted track width.....23.62 inch  
Overall width.....86.6 inch  
Overall machine length.....129 inch

**Capacities:**

Fuel.....15.8 us.gal  
Hydraulic oil.....23.7 us.gal  
Weight (Base machine) .....5621 lbs  
Payload.....4409 lbs

**Rear 3-Point linkage:**

Category one 3-point linkage with stabilisers and adjustable lift arms.  
Maximum lift capacity at the end of the arms.....2645 lbs  
Rated capacity.....1543 lbs

**Front linkage:**

Category one front linkage with articulating lower lift arms.  
Maximum lift capacity at the end of the arms.....2314 lbs  
Rated capacity .....1322 lbs

**PTOs:**

Hydrostatic drive to a 540 rpm motor at the rear and quick connect flat-faced couplings at the front or rear.  
Rear PTO motor power (540 rpm).....73.7 hp  
Front hydraulic PTO power.....73.7 hp  
Front/rear hydraulic PTO oil flow (2,000rpm).....27.4 us.gal /min  
Maximum pressure.....5800 psi

